

: 17/07-09-2016 (: 75 46530 - 2), 26/ 04-10-2012 (: 4 81-70)

	μ.		1501- +	(17/07-09-2016)	
μ					
20.05.01	1	E μ - μ μ μ μ	02-04-00-00		
20.04.01	2	E μ μ - μ μ	02-04-00-00		
\22.04	3	μ μ	14-02-02-01		
22.10.01	4	μ μ , μ	15-02-01-01		
22.20.01	5				
.22.20.01	6				
22.22.02	7	μ μ , 50%			
22.36.01	8	μ μ μ , 0,51 m2 1,00 m2			
22.51	9	μ			
22.72	10	o μ μ			
22.45	11	μ			
.20.30	12	μ μ , μ μ ,			
\ 20.42	13	μ μ ,			
32.01.03	14	μ μ μ μ , μ μ μ μ C12/15	01-01-01-00 *	μ	01-01-01-00
			01-01-02-00		
			01-01-03-00 *	μ	01-01-03-00
			01-01-04-00 *	μ μ	01-01-04-00
			01-01-05-00		
			01-01-07-00		

	μ.		1501- +	(17/07-09-2016)	
μ					
32.01.04	15	μ , μ μ , μ μ μ μ C16/20	01-01-01-00 *	μ	01-01-01-00
			01-01-02-00		
			01-01-03-00 *	μ	01-01-03-00
			01-01-04-00 *	μ μ	01-01-04-00
			01-01-05-00		
			01-01-07-00		
32.25.02	16	μ μ μ , 30,00m3 μ C12/15			
32.25.03	17	μ μ μ , 30,00m3 μ C16/20			
38.03	18		01-04-00-00		
38.20.02	19	μ μ , B500C.	01-02-01-00 *	μ μ	01-02-01-00
38.20.03	20	μ μ , μ μ B500C	01-02-01-00 *	μ μ	01-02-01-00
23.03	21	μ	01-03-00-00 *	μ	01-03-00-00
.43.01.03	22	μ μ μ μ μ μ 400 kg μ 0,08 m3	03-02-01-00		
.43.06.02	23	μ μ μ μ μ 400 kg μ 0,08 m3	03-02-01-00		
1.77.34	24	μ μ μ μ .	08-07-02-01		
71.36	25	μ ()	03-03-01-00		
.71.01.03	26	μ μ μ			
18732.1.6	27	μ μ μ μ μ 25 (μ) , μ μ μ μ			
62.10.41.01	28	E1VV-U, -R, -S (), μ. 600/1000 V μ μ μ PVC μ 3 x 1,5 mm2			
8735.2.1	29	70mm			
8840.1.2	30	μ μ μ μ μ 50 35 cm 30 μ			
8880.1.2	31	μ μ μ μ μ 5 SIEMENS 40			

	μ.		1501- +	(17/07-09-2016)	
μ					
8915.1.2	32	μ WL-SIEMENS μ μμ 10			
\8880	33	μ μ 40			
\8924	34	() μ 500 V			
\8827.3.2	35	μ SCHUKO			
\8801.1	36	μ 10 250 V			
\8973.3.5	37	μ LED, IP 65, 36W, μ 1,2μ			
\8982.9.1	38	μ 4000 , LED 50W , μ			
72.03	39	μ μ μ , μ , μ	03-05-01-00		
73.11	40	μ	03-07-03-00 *	μ	03-07-03-00
73.12	41	μ μ	03-07-03-00 *	μ	03-07-03-00
73.93	42	μ μ μ			
.72.03	43	μ μ μ μ μ , μ , μ	03-05-01-00		
52.02.02	44	μ μ	03-07-01-01		
52.13	45	()			
52.76.01	46	μ			
52.79.02	47				
52.80.01	48	μ μ			
52.80.03	49	μ μ 2,5 cm			
52.90.01	50	5,00 m μ (), μ			
54.20.01	51	o , μ , μ , μ 9x9 cm	03-08-01-00		
54.36	52	E	03-08-01-00		
.54.56	53				
\ 3.64.10.03	54	μ μ μ 20mm			
76.27.01	55	μ μ - μ - 8 mm, 5 mm) 18 mm, (5 mm,	03-08-07-02		
77.01	56	μ μ	03-10-02-00		

	μ.		1501- +	(17/07-09-2016)	
μ					
77.71.03	57	μ μ μ μ	03-10-05-00		
79.10	58	μ μ μ μ μ μ			
79.16.01	59	μ μ 0,40 mm μ			
79.32	60	μ μ μ μ	03-06-02-02 *	μ μ	03-06-02-02
77.96	61				
3.10.02.01	62	μ μ μ 3,00 m, μ μ 4,00 m	08-01-03-01		
5.05.01	63	μ μ μ μ μ μ μ μ 50 cm	08-01-03-02 *	μ	08-01-03-02
5.04	64	μ μ μ μ μ μ	08-01-03-02 *	μ	08-01-03-02
4.09.01	65	μ μ μ μ 5 cm			
12.10.04	66	μ μ μ μ PVC-U μ PVC-U, SDR 41, DN 200 mm	08-06-02-02 *	-PVC	08-06-02-02
64.2	67	μ μ μ μ			
.16.14.01	68	μ μ μ μ μ μ 1917, 1,20 -1,50m			
. 07	69	μ μ μ μ μ μ			
11.02.04	70		08-07-01-04		
11.01.02	71	K μ μ μ μ (ductile iron)			
\8218.2	72	μ μ μ μ 1,5HP - 220V ()			
9316.3	73	μ μ μ μ 1 ins			

	μ.		1501- +	(17/07-09-2016)	
μ					
01	74	μ	μ	μ	

20-4-2018

20-4-2018

20-4-2018

μ

3

μ

3

5

μ /

4